





Specialty



With its open grid diamond pattern, Modular Lok-Tyle™ allows moisture and debris to drain from the surface and aids traction. The modular cross-hatch PVC vinyl tiles snap together on-site for custom configurations. Its lightweight, modular design allows for additional use as shelf liners in food prep and bar areas.

<u>Test</u>	Test Description	* <u>Results</u>
Compression Deflection	Test specimen is subjected to varying compression load levels and the resulting deflection was measured. The greater the deflection, the better the anti-fatigue properties. (Inches)	.143" (40 lbs/sq. inch)
Coefficient of Friction ASTM C1028-96	A neolite heel assembly with a predetermined load is pulled horizontally with a dynamometer to measure the force required to cause the assembly to slip.	.71
Abrasion Resistance ASTM D3884-01	Test specimen is subjected to the rubbing action of two abrading wheels under controlled conditions. Results measured in Weight loss (Grams)	(no data available at this time)
Elongation ASTM D412	Test specimen is stretched at a specified rate until breaking point. The results are measured in % of size increase at breaking point.	N/A
Critical Radiant Flux ASTM E648-94A	The test result is an average critical radiant flux (watts/square cm) which indicates the level of radiant heat energy required to sustain flame propogation in the flooring system.	(no data available at this time)

^{*}All testing of NoTrax® floor matting has been performed by an independent testing laboratory.



Food Service



Custom Configurations



Anti-Slip



Drainage/Wet Areas



Food Processing



Anti-Fatigue

- Solid PVC vinyl construction: highly resistant to industrial chemicals
- Raised diamond porthole system facilitates drainage and aids traction
- Overall thickness: 9/16"
- Beveled ramps and corners for safe, easy access
- Stock Sizes: 12" x 12" Tile, 2" x 12" Ramp, 2" x 2" Corner



