

A sleek, modern under-cabinet lighting fixture is shown in a close-up, angled view. The fixture is a long, thin, metallic bar with several small, circular LED lights embedded along its length. It is mounted to a light-colored surface, likely a cabinet. The background is a soft, out-of-focus teal and blue gradient with large, overlapping circular shapes in shades of green and yellow. The word "Verano" is written in a large, light blue, sans-serif font across the top of the image, with a smaller "Verano™" logo above it.


Verano™

The Future of Under-cabinet Lighting is Here

Verano's elegant slender profile uses significantly less energy and raw materials than traditional fluorescent fixtures. Its next-generation LEDs provide superior light output, bringing the warmth and brightness of natural daylight to the desktop. Verano further exceeds expectations with its unique mounting system that allows users to rotate or slide the fixture as desired. Plus, project managers will appreciate Verano's lightning fast install and LEED credit eligibility. Eco and user friendly, Verano is the natural choice.

Workrite
ergonomics®

Verano™ Under-Cabinet Lighting



- Three lengths: 24", 36", 48" (nominal)
- Ultra-slim 1 1/8" x 1" profile
- Fixture rotates +/-20°
- Magnetic rotating and fixed mounts for rapid installation to steel shelving
- Wood shelf rotating and fixed mounts included
- All mounts allow for lateral adjustment without track
- 50,000 hour, 20 year lifetime
- Color temperature: 3500K, CRI:92
- Single push button power switch
- Cord clips included
- 48" jumper cord for all daisy chain units
- 10 year warranty; UL listed, cUL listed
- Available in 3 colors: Winter, Sterling and Carbon (custom colors for 200 min. quantity, consult factory for pricing)
- Post-consumer recycled content used in packaging; aluminum housing all recyclable at end of life
- Water-based paint used for all finishes
- Meets DOE Ergonomics Guidelines and IESNA RP-1-04 section 2.3 requirements for task lighting illuminance levels
- Energy Star credential in process

Configuration	Nominal length	Actual length	Model #	Color	Weight
Single Unit	24" †	19 1/4"	VER-24-	<input type="checkbox"/>	2
	36" †	27 3/8"	VER-36-	<input type="checkbox"/>	3
	48" †	35 3/8"	VER-48-	<input type="checkbox"/>	4
2 Unit Daisy Chain	24" †	19 1/4"	VER-24-2PK-	<input type="checkbox"/>	4
	36" §	27 3/8"	VER-36-2PK-	<input type="checkbox"/>	6
	48" §	35 3/8"	VER-48-2PK-	<input type="checkbox"/>	8
3 Unit Daisy Chain	24" §	19 1/4"	VER-24-3PK-	<input type="checkbox"/>	6
	36" §	27 3/8"	VER-36-3PK-	<input type="checkbox"/>	9
4 Unit Daisy Chain	24" §	27 3/8"	VER-24-4PK-	<input type="checkbox"/>	8

Colors: **W**-Winter, **S**-Sterling, **C**-Carbon

† Configured with a 9' cord and a 2 amp, 12v transformer with two prong plug: 2 3/4"H x 2"W x 1"D

§ Configured with a 6' cord connecting to a 4 amp, 12v transformer 4 1/2"L x 2 1/4"W x 1 1/2"H and a 4 1/2' cord with standard two prong plug

LEED credit eligibility

- Energy and atmosphere, credit 1.1
 - Optimize energy performance: lighting power (1-3 points)
- Innovation in design, credit 1.1-1.4
 - Implementation of comprehensive ergonomic program (1-4 points)

Specifications:

Lengths

Actual Fixture Length	Compatible Shelf Width	Number of LEDs	Total Wattage
19 1/4"	24"	8	8W
27 3/8"	36"	12	12W
35 3/8"	48"	16	16W


Photometrics

Source at 18"

inches	18	12	6	0	6	12	18
12	14.6	31.1	46.0	49.5	43.9	26.4	10.0
9	26.7	60.0	86.8	93.9	82.1	47.4	17.6
6	41.0	94.2	137.4	147.6	125.9	70.3	26.5
3	54.8	122.4	152.6	165.9	140.5	88.2	33.7
0	59.7	115.0	144.8	154.6	127.9	85.5	35.7
3	55.8	114.6	140.9	154.4	128.4	82.8	32.8
6	43.8	92.6	130.6	141.3	115.1	67.5	25.0
9	26.2	57.9	83.0	89.1	72.7	42.9	16.1
12	14.3	29.6	42.3	45.2	38.1	22.7	9.4


Model # tested: VER-36
Average illuminance under fixture: 87 footcandles

Rotation*



* Fixed, non-rotating kit included as standard

Actual Size (rotating mount)



800.531.3746 • info@thehumansolution.com • thehumansolution.com