



Superior
Manufacturing
Group, Inc.

549 Safety Stance® Anti-Fatigue/Anti-Slip Matting



Available Colors: Black/Orange, Black/Yellow

Good Better Best Superior



Safety Stance® is made from a grease resistant rubber compound to withstand many of the more commonly found industrial cutting oils and chemicals. Particularly well suited for wet or dry work areas, Safety Stance® features a large hole drainage system with a mini-diamond studded top surface to minimize slippage.

Test	Test Description	*Results
Compression Deflection	Test specimen is subjected to varying compression load levels and the resulting deflection was measured. The greater the deflection, the better the anti-fatigue properties. (Inches)	.871" (40 lbs/sq. inch)
Coefficient of Friction ASTM C1028-96	A neolite heel assembly with a predetermined load is pulled horizontally with a dynamometer to measure the force required to cause the assembly to slip.	.93
Abrasion Resistance ASTM D3884-01	Test specimen is subjected to the rubbing action of two abrading wheels under controlled conditions. Results measured in Weight loss (Grams)	(data currently unavailable)
Elongation ASTM D412	Test specimen is stretched at a specified rate until breaking point. The results are measured in weight needed to break, and % of size increase at breaking point.	258.2% (average of 5 specimens)
Hardness ASTM D2240-02	The hardness of a test sample is measured by means of a type A Shore Durometer. It measures the penetration of its specified indenter forced into the material under specified conditions	33

*All testing of NoTrax® floor matting has been performed by an independent testing laboratory.



Anti-Fatigue



Drainage



Anti-Slip



Welding

- Colored beveled borders are permanently affixed on either 3 or 4 sides
- Thickness: 7/8"
- Stock Sizes: 26" x 40", 28" x 40", 38" x 40", 40" x 40", 38" x 64", 40" x 64", 38" x 124", 40" x 124"



RESULTS from INDEPENDENT TEST LABS & PRESENTED as COMPARISONS to OTHER NoTRAX® INDUSTRIAL MATS