





Good Better Superior



Sanitop® is made from a durable rubber compound formed with an alternating large and small hole drainage system to keep liquid and debris free from the work area. Designed to withstand harsh chemicals while creating a slip resistant surface, Sanitop® offers a simple, economical solution to almost any industrial or food service application.

<u>Test</u>	Test Description	* <u>Results</u>
Compression Deflection	Test specimen is subjected to varying compression load levels and the resulting deflection was measured. The greater the deflection, the better the anti-fatigue properties. (Inches)	.780" (40 lbs/sq. inch)
Coefficient of Friction ASTM C1028-96	A neolite heel assembly with a predetermined load is pulled horizontally with a dynamometer to measure the force required to cause the assembly to slip.	.67
Abrasion Resistance ASTM D3884-01	Test specimen is subjected to the rubbing action of two abrading wheels under controlled conditions.  Results measured in Weight loss (Grams)	(data currently unavaialable)
Elongation ASTM D412	Test specimen is stretched at a specified rate until breaking point. The results are measured in weight needed to break, and % of size increase at breaking point.	227.7% (average of 5 specimens)
Hardness ASTM D2240-02	The hardness of a test sample is measured by means of a type A Shore Durometer. It measures the penetration of its specified indentor forced into the material under specified conditions	52

\*All testing of NoTrax® floor matting has been performed by an independent testing laboratory.



Anti-Fatigue

Available Colors: Black, Red



Anti-Slip



Drainage



Food Service



Food Processing

- Available in two versions:
  - Black: NBR (Natural Rubber) grease resistant w/1 year warranty
  - Red: Nitrile Rubber grease proof w/3 year warranty
- Thickness: 1/2"
- Molded beveled borders on 4 sides
- Stock Sizes: 3' x 5', 3' x 10', 3' x 20'



