

# Slatwall and SlatRail



A Steelcase Company

details



# Slatwall and SlatRail help expand space.

Panel mounted, wall-mounted, or desk-mounted. Regardless the application, Slatwall or SlatRail help expand space, eliminate clutter and increase workplace productivity.





Obligatory and important basic feature information.

#### Support System Comparison

	Slatwall	SlatRail	SOTO
Panel-mount	Yes	Yes	No
Wall-mount	Yes	Yes	No
Freestanding mount available	Yes	Yes	Yes
c:scape™ desk rail system	Yes	Yes	Yes
Context® Stanchion compatible	Yes	No	No
Corner Application	No	No	No
Maximum support weight	60 lbs.	100 lbs.	125 lbs.
Number of compatible worktools	32	28*	12
Number of available widths	6	6	7
Horizontal flexibility	Yes	Yes	Yes
Vertical flexibility	Yes	No	No
Maximum overhang from panel connection	12" **	12" **	N/A

\* The following should not be specified for SlatRail: Hanging Brackets (WHB) on stanchion-mounted SlatRail, Jules Slatwall-mounted keyboard platform (KJULES), Markerboard (WMB), Universal Shelf (WUS, WUS3)

\*\* 15" overhang for 60" wide applications; 12" overhang for all other sizes

#### Determining the Width

For panel-mounted applications, simply measure the distance between the two panel channels that the mounting brackets will be on. This is the minimum required width. You may order up to an additional 12" of width to overhang each non-corner channel and overlap the adjacent panel (60" applications can support a 15" overhang). The furniture system determines the appropriate mounting bracket to order.

#### Determining Available Space

The worktools to be mounted cannot exceed the space available on the Slatwall or SlatRail you are ordering.

#### Wall-mount Applications

Brackets should be installed into wall studs. You may order up to an additional 12" of width to overhang each bracket. (60" applications can support a 15" overhang).

#### Panel- or Wall-mount Applications

Slatwall requires a minimum of 13" of vertical space between the worksurface and any shelves or bins in a panel or wall-mount application. When stacking Slatwall tiles in either a panel or wall mount application, a gap of approximately 1/2" occurs.

#### 12" Slatwall Tile Applications Only

Stanchion Mount Applications - Stanchion mount applications require a minimum of 15 1/2" of vertical space between the worksurface and any shelves or bins.

Context® Slatwall Stanchion Mount Applications - Tile must be 10" shorter than core unit if utilizing Context columns to support overhead bins, shelves, etc.

#### Freestanding Product Applications

Simply make sure the dimensions of the worktools fit in the available space on the worksurface.

#### Style Numbers/Descriptions

Slatwall Tiles	12" H Tiles	18" H Tiles
24" wide	WS24	WS2418H
30" wide	WS30	WS3018H
36" wide	WS36	WS3618H
42" wide	WS42	WS4218H
45" wide	WS45	WS4518H
48" wide	WS48	WS4818H
60" wide	WS60	WS6018H

W as ordered x H12 or 18 x D 1/2 (with end caps installed)

Supports maximum of 60 lbs.

Slatwall Tiles: Black, Champagne, Platinum

#### 12" H Slatwall Tile Brackets

WFCS - Freestanding Slatwall Stanchions

WSWM - Wall Mount Brackets

WSWANS - Panel Mount Brackets (Answer/Kick/Privacy Wall)

WSWUSA - Universal Panel Mount Brackets

WSWPBOF12 - On Post and Beam Brackets

DSWCS - c:scape™ Bracket

#### 18" H Slatwall Tile Brackets

WSWM18 - Wall Mount Brackets

WSWUSA18 - Universal Brackets

WSWANS18 - Panel Mount Brackets (Answer/Kick/Privacy Wall)

#### SlatRail

24" wide WSR24

30" wide WSR30

36" wide WSR36

42" wide WSR42

48" wide WSR48

60" wide WSR60

W as ordered by H4" x D 3/4"

Supports maximum of 100 lbs.

SlatRail: Black, Champagne, Platinum

#### SlatRail Brackets

WSRFS - Freestanding SlatRail Stanchions

WSRW - Wall Mount Brackets

WSRUI - Panel Mount Brackets

Panel Mount, Wall Mount, On Post and Beam Brackets and Freestanding SlatRail Stanchions Finishes: Black, Champagne and Platinum. c:scape Bracket Finish: Platinum

NOTE: Slatwall Bracket for c:scape allows for any size Details Slatwall to easily mount to the Steelcase c:scape desk rail system only. Not applicable on c:scape beam or storage units. Allow for 5 1/4" clearance on each end of the worksurface for mounting on c:scape desks.

Other brackets available. Please refer to the online version of the Details SpecGuide for current pricing and information.

Organizational logic and ergonomic well-being.



available at:



800.531.3746  
info@thehumansolution.com  
thehumansolution.com

For a better day at work.®

**details**

A Steelcase Company