

### INTENDED USES

This customizable urethane is a perfect combination of extremely high performance and exceptional comfort. **A premium urethane compound, Rejuvenator Connect will not crush down!** In fact, it has a **10 Year Resilience Warranty!** The robust, abrasion resistant exterior skin encapsulates a resilient, crush-resistant urethane sponge creating a virtually indestructible mat. Modular and designed with an effective interlocking system on all four sides these mats snap together and stay together. Use in dry areas.

### WARRANTY

5 Year Limited Warranty (see Limited Warranty section below for more details)  
10 Year Resiliency Warranty

### DETAILS AND COMPOSITION

<b>Compound</b>	100% Urethane
<b>Edges</b>	Optional 2" x 39" beveled safety ramps
<b>Thickness</b>	5/8"
<b>Overall Weight</b>	1.3 lbs. sq. ft
<b>Size</b>	3' x 3' modular tiles
<b>Custom Sizes</b>	Can be customized in any size or shape.
<b>Colors</b>	Mat: Black Beveled Edges: Black or Yellow

### TEST SPECIFICATIONS AND RESULTS

<b>Property</b>	<b>Test</b>	<b>Results</b>
<b>Flammability (surface)</b>	MVSS 302	"A" Rating. It has a flame spread of < 1.6 and is labeled self-extinguishing.
<b>Coefficient of Friction</b>	ASTM F1677	Dry: COF = .75 Wet: COF = .28
<b>Tabor Abrasion</b>	Federal Standard 191	<1% lost @ 1,000 cycles
<b>Elongation</b>	ASTM D412	Longitudinal > 125%
<b>Density (sponge)</b>	Wearwell Requirements	> 20 lbs./ft <sup>3</sup>
<b>Accelerated Compression</b>	ASTM D 395-98	< 10%
<b>Ozone Resistance</b>	ASTM D 1171	Excellent
<b>Temperature Range</b>	ASTM D 1056	-50 to 250 degrees Fahrenheit
<b>Compression Set Under Constant Deflection, 25% (Suffix B), 72%</b>	ASTM D 395	30 minutes – 5.67 24 hours – 1.42

<b>Resilience by Vertical Rebound</b>	ASTM D 2632-01	6.50
		6.25
		6.25
		6.75
		<u>6.50</u>
		6.45

## CHEMICAL RESISTANCE (SURFACE)

<b>Chemical</b>	<b>Ranking</b>	<b>Chemical</b>	<b>Ranking</b>
Acetic Acid 30%	Good	Nitric Acid (dilute)	Good
Acetone	Good	Nitric Acid 30%	Good
Ammonium Hydroxide	Good	Potassium Permanganate (dilute)	Good
Brake Fluid	NR	Styrene	Good
Butyl Alcohol	Good	Sulfuric Acid 25%	Good
Most acids	Good	Toluene	Good
Most alkalis	Good	Water	Good

**Note:** This information should be used as a guide and is based on surface chemical spills. It is also assumed that the chemical will be cleaned off within a reasonable amount of time. Please call for additional results, technical assistance or to request a small sample for testing.

## CLEANING RECOMMENDATIONS

Sweep regularly or dry mop the surface. These mats can be wet mopped with mild soap or detergent. For best results use a detergent like Ivory Liquid with a ph between 4.0 – 9.0.

## HOW TO REACH US

For more information or to place an order, call 1-800-264-3030. To view this product in color, please visit our website, [www.wearwell.com](http://www.wearwell.com).

## LIMITED WARRANTY

The materials and workmanship used in the construction of the Rejuvenator Mats are guaranteed under normal conditions of usage for five years after the date of shipment.

If the purchaser discovers a defect in the materials or workmanship of a Wearwell® mat within the warranted time after the date of shipment, Tennessee Mat Company, Inc. will, at its own discretion, either i.) repair the nonconforming product, ii.) replace the product with the same or substantially similar product, or iii.) reimburse the buyer for the pro-rated purchase price of the nonconforming product.

Tennessee Mat Company reserves the right to inspect the non-conforming mat(s) before repairing, replacing or reimbursing the buyer. Therefore, at the preference of Tennessee Mat Company, Inc., the mats must be returned or available for on-site inspection. Modifying or installing the mat may void the warranty. The decision to void this warranty will be made at the sole discretion of Tennessee Mat Company.

To the maximum extent permitted by law, Tennessee Mat Company's liability shall not exceed the purchase price of the product; Tennessee Mat Company shall not be liable for any incidental, consequential, special, and indirect or punitive damages (including without limitation, damages from lost business, profits or goodwill).

## 10 year Resilience Warranty for Wearwell Urethane Products

The urethane material used in the construction of Rejuvenator No. 501, Rejuvenator Connect No. 502 and Pur-Comfort No. 504 is guaranteed to not crush down under normal conditions of usage for ten years after the date of shipment. Normal conditions include, but are not limited to: 1. dry area use only, 2. no heavy cart or tow-motor traffic, and 3. use as an anti-fatigue mat for human workers. If the material does crush down within this warranted time after the date of shipment, Tennessee Mat Company, Inc. will, at its discretion, either i.) replace the product with the same or substantially similar product, or ii.) reimburse the buyer for the pro-rated purchase price of the nonconforming product.

Tennessee Mat Company reserves the right to inspect the non-conforming mat(s) before replacing or reimbursing the buyer. Therefore, at the preference of Tennessee Mat Company, Inc., the mats must be returned or available for on-site inspection. Modifying or installing the mat may void the warranty. The decision to void this warranty will be made at the sole discretion of Tennessee Mat Company.

To the maximum extent permitted by law, Tennessee Mat Company's liability shall not exceed the purchase price of the product; Tennessee Mat Company shall not be liable for any incidental, consequential, special, and indirect or punitive damages (including without limitation, damages from lost business, profits or goodwill).

available at:



800.531.3746

[info@thehumansolution.com](mailto:info@thehumansolution.com)

[thehumansolution.com](http://thehumansolution.com)