

SMALL IN SIZE, BIG IN PERFORMANCE

The Astra 2 Single Arm LED task light is designed to provide high performance lighting in work environments where space is at a premium. Astra 2 features clustered, high output, high CRI LEDs that provide a crisp, white light with no shadowing effect.

The new touch button programmability enables the user to return to the same dimming level that the light was last used, double touch the control to move to maximum brightness instantaneously, or to program the light for auto shut off after 5 or 10 hours of use. When combined with our new Tool Bar/ Slatwall Mount, the Astra 2 Single Arm task light is the ultimate space saving solution.



auto shut-off programming and brightness memory.



Available with four mounting/ base options including a space saving Tool Bar mount.



ASTRA 2 SINGLE ARM LED DESK LIGHT


Astra 2 Single Arm

Single Arm Luminaire


- Compact, space saving design
- Exceptional light color accuracy (94 CRI)
- Multiple mounting options
- Programmable auto shut-off
- Brightness memory (dimming to 5%)
- Secure mounting lock
- Occupancy sensor compatible
- Available in Silver & Charcoal
- ETL Certified/UL Listed
- Energy Star Compliant (luminaries v 1.2)
- 50,0000+ hour LED life (L70 rating)
- 5 year fixture warranty
- Transformer included:
 - Type A, wall plug transformer with 6' cord
 - 12 W, 24 V, 0.5 A, Class 2

Dimensions

Horizontal and vertical reach











Color

Silver

Charcoal

Model#

AST2-SA-WOB-S

AST2-SA-WOB-C

Weight

List

\$270

\$270

Shade pivot

Shade rotation

Specifications

Foot Candle Power (@ 15"): 106 fc
Light Output (lumens): 306 lm
Power Consumption (wattage): 6.1 W
Lumens per Watt: 50 lm/W
Light color temperature (CCT): 3200 K
Color Rendering Index (CRI): 94 CRI

Photometrics

Source at 15"

15" 12" 9" 6" 3" CL 3" 6" 9" 12" 15"

15" 3 4 5 8 8 7 5 4 3 2 Footcandle Power

12" 3 5 8 11 15 17 14 10 7 4 2

120-140

9" 4 9 15 25 33 36 31 22 14 6 3

6" 5 12 23 44 63 67 57 40 20 11 4

3" 6 14 32 60 88 98 88 59 31 13 6

CL 7 16 35 65 97 106 95 66 36 14 6 60-80

3" 6 14 32 59 85 97 86 58 29 12 5

40-60

6" 5 12 22 40 56 65 61 42 21 10 4

9" 3 11 14 23 31 34 32 22 12 6 3

12" 2 4 6 10 15 16 13 11 6 3 2

Colors



ASTRA 2 SINGLE ARM LED DESK LIGHT

Base & Mounting Options (required)		Color	Model #	Weight	List
Table Base	Sturdy yet movable, this 4 pound table base lets you put your light exactly where you want it	Silver	LTG-TB-ST-S	4	\$35
		Charcoal	LTG-TB-ST-C	4	\$35
	• Dimensions: 7.5"W × 9"D × .4"H		•		
USB Table Base	Convenient USB power port allows users to charge a phone or tablet device with a Type A USB power cable (USB cable not included)	Silver	LTG-TB-USB-S	4	\$55
		Charcoal	LTG-TB-USB-C	4	\$55
	• Power Output: 5 V, 1100 mA, 5.5 W				
	• Dimensions: 7.5"W × 9"D × .4"H				
Two Piece C-Clamp Mount	The sturdiest and most compact mounting solution	Silver	LTG-CCB-TP-S	1	\$20
	 Two piece design provides easy installation in space constrained environments 	Charcoal	LTG-CCB-TP-C	1	\$20
	• Attaches to surfaces .25" – 2.5" thick				
	• Dimensions: 2"W × 1.75"D × 4.5" H				
Tool Bar, Slatwall Mount	Add some height to your light and conserve desk space, by mounting it to a Workrite Tool Bar	Silver	LTG-TSB-ADJ-S	1	\$35
		Charcoal	LTG-TSB-ADJ-C	1	\$35
	 Adjustable clamp design is also compatible with any 90° edge .5" – 1.75" Slatwall system 				
	• Dimensions: 2.5"W × 2"D × 2.8"H				

Optional Accessories


Occupancy Sensor




- Add to Astra models for energy savings
- Turns light off after 15 minutes of inactivity and instantly back on when activity is detected
- Swivels to direct sensor to area of activity


Silver LTG-OCC-SWVL-S 1 \$55 stantly Charcoal LTG-OCC-SWVL-C 1 \$55

TR-12240500-A-SF3.5





Black



\$22

Replacement Parts

Astra Replacement Transformer

- Type A, wall plug transformer with 6' cord
- 12 W, 24 V, 0.5 A, Class 2



ASTRA 2 SINGLE ARM LED DESK LIGHT

PRODUCT COMPARISON: DESKTOP TASK LIGHTING

	Astra 2	Astra 2	Fundamentals	Natural
CONFIGURATION	Double Arm	Single Arm	Single Arm	Single Arm
LIGHT OUTPUT				
Foot Candle Power (@ 15")	106 fc	106 fc	78 fc	108 fc
Peak Lumen Output	306 lm	306 lm	184 lm	442 lm
Color Temperature	3200 K	3200 K	3200 K	3900 K
CRI	94	94	81	94
Dimming	Continuous down to 5%	Continuous down to 5%	Continuous down to 15%	Two step
ENERGY EFFICIENCY				
System Power Consumption	6.1 W	6.1 W	3.4 W	13.7 W
Lumens per Watt	50 lm/W	50 lm/W	54 lm/W	32 lm/W
PIR Occupancy Sensor Option	•	•		
Programmable Auto Shutoff	•	•		
L70 Estimated Life	50,000+ hours	50,000+ hours	40,000+ hours	30,000+ hours
FIXTURE HOUSING				
Reach	34.5"	19.5"	14.5"	10.5"
Shade Rotation	360°	360°	360°	
Shade Tilt/Pivot	160°	160°		
User Controls/ Switch Type	Programmable touch button	Programmable touch button	Touch button	Touch button
Number of LED's In Fixture	6	6	21	One OLED panel
MOUNTING OPTIONS Table Base	•	•	•	•
USB Table Base	•	•		
Two Piece C-Clamp Mount	•	•		
Tool Bar/Slatwall Mount	•	•		
Available Fixture Colors	Silver & charcoal	Silver & charcoal	Silver	Silver
WARRANTY				
Fixture	5 years	5 years	5 years	5 years
Transformer	1 year	1 year	1 year	1 year



